

## AMENDMENTS TO THE CLAIMS

Claim 1 (currently amended): A bipolar junction transistor (BJT) comprising:

- 5 a substrate;
- a dielectric layer formed on a predetermined region of the substrate;
- an oxide layer and a silicon nitride layer stacked on the dielectric layer;
- 10 an opening formed in the dielectric layer, the oxide layer, and the silicon nitride layer, and a portion of the substrate being exposed;
- a heavily doped polysilicon layer formed on a sidewall of the opening and on the substrate to
- 15 define a self-aligned base region in the opening;
- an intrinsic base doped region formed within the substrate and in a bottom of the opening by implanting through the self-aligned base region;
- a spacer formed on the heavily doped polysilicon
- 20 layer to define a self-aligned emitter region in the opening; and
- an emitter conductivity layer being filled ~~with~~ into the self-aligned emitter region, and a PN junction being formed between the emitter
- 25 conductivity layer and the intrinsic base doped region.

Claim 2 (original): The bipolar junction transistor of claim 1 wherein the heavily doped polysilicon layer

30 is doped with a boron dopant with a dosage ranging from  $1E19$  to  $1E21$  atoms/cm<sup>3</sup>.

Claim 3 (original): The bipolar junction transistor of claim 1 wherein the substrate is a silicon substrate.

5 Claim 4 (original): The bipolar junction transistor of claim 1 wherein the substrate is a non-selective epitaxial silicon substrate.

10 Claim 5 (original): The bipolar junction transistor of claim 1 further comprising a self-aligned silicide (salicide) layer formed on the emitter conductivity layer.

15 Claim 6 (original): The bipolar junction transistor of claim 1 further comprising a selective implant collector (SIC) region formed in the substrate beneath the intrinsic base doped region.

20 Claim 7 (currently amended): The bipolar junction transistor of claim 1 further comprising an extended conductivity layer formed on the silicon nitride ~~dielectric~~ layer electrically connected to the heavily doped polysilicon layer.

25 Claim 8 (canceled)

Claim 9 (original): The bipolar junction transistor of claim 7 wherein the extended conductivity layer is composed of in-situ doped polysilicon.

30 Claim 10 (canceled)

Claim 11 (currently amended): A hetero-junction bipolar

junction transistor (HBT) comprising:

a substrate;

a dielectric layer formed on a predetermined region of the substrate;

5 an opening formed in the dielectric layer, and a portion of the substrate being exposed;

a SiGe epitaxial layer formed on a sidewall and a bottom of the opening, and extending outside the opening and above the dielectric layer;

10 a spacer formed on the SiGe epitaxial layer to define a self-aligned emitter region in the opening; and

an emitter conductivity layer being filled with into the self-aligned emitter region, and a PN  
15 junction being formed between the emitter conductivity layer and the SiGe epitaxial layer.

Claim 12 (original): The hetero-junction bipolar junction transistor of claim 11 wherein the substrate  
20 is a silicon substrate.

Claim 13 (original): The hetero-junction bipolar junction transistor of claim 11 wherein the substrate is a non-selective epitaxial silicon substrate.

25 Claim 14 (original): The hetero-junction bipolar junction transistor of claim 11 further comprising a self-aligned silicide (salicide) layer formed on the emitter conductivity layer.

30 Claim 15 (original): The hetero-junction bipolar junction transistor of claim 11 further comprising a

selective implant collector (SIC) region formed in the substrate beneath the SiGe epitaxial layer.

Claim 16 (canceled)

5

Claim 17 (canceled)